



Re-board®
TECHNOLOGY

Re-Board® Basic

Re-board® Basic is a lightweight yet exceptionally strong and fully recyclable paperboard. The unique engineered fluted core of Re-board® ensures excellent planar flatness combined with design flexibility to create almost any shape.

Printing and Finishing

Re-board® Basic can be digitally printed or finished with decorative laminates to achieve stunning results. It is a versatile board good printability and high performance. The unique engineered fluted core enables a Re-board® sheet to be rapidly cut into any conceivable shape.



The liner in Re-board® Basic is made of 100% recovered fibres from the Nordic countries making it one of the strongest board qualities on the market.

Exclusive Accessories

Re-board® comes with a wide range of exclusive accessories, including screws, edge bands, corner locks, hooks and more.



Sustainability

Re-board® Basic contains no harmful components and utilizes water-based adhesives. The board can be recycled as paper in normal waste paper streams found throughout the world.

Carbon Footprint

Re-board® is first rigid paperboard in the world to independently measure its CO2 emissions. 16mm Re-board CO2 emission/sqm = 2 kg, based on CEPI and ISO 14040 guidelines.



Certified Management Systems

The Norrköping mill is FSC Chain of Custody certified according to FSC-STD-40-004 ver 2.1.



The mark of
responsible forestry

Certified Management Systems

Re-board[®] Basic is produced in Norrköping, Sweden.

Technical Data	
Liner grammage (g/m ²)	325
Whiteness (ISO D65/10, %)	84
Brightness (ISO R457, %)	79
Width (mm)	1220, 1600
Length (mm)	Standard: 2200, 2400, 2440, 3200 Range: 1500-3500
Thickness (mm)	Standard: 10, 16 Range: 8-35
Weight (kg/sqm)	1.4 (10mm), 1.8 (16mm)
Tolerance, corner curvature from flat (mm)	<10
Tolerance in length, general (mm)	± 3

